

ATTORNEY DOCKET No. 10693RMUS01U (NORT10-00255)
U.S. SERIAL No. 09/468,138
PATENT

PENDING CLAIMS:

- 1 1. (Currently Amended) An apparatus for generating a hybrid speech model associated to a given speech element, said hybrid speech model being suitable for use by a speech recognition device during speech recognition, said apparatus comprising:
 - 4 - an input for receiving an input signal derived from a spoken utterance that contains at least one speech element that potentially matches the given speech element;
 - 5 - a model group associated to the given speech element, said model group comprising a plurality of speech models, each speech model of said plurality of speech models being a different representation of the given speech element;
 - 6 - a processing unit coupled to the input for processing the input signal and the model group to generate a hybrid speech model associated to the given speech element, said hybrid speech model being a weighted combination of speech models in said plurality of speech models effected on the basis of the input signal derived from the spoken utterance;
 - 7 - an output for releasing a signal indicative of said hybrid speech model associated to the given speech element in a format suitable for use by a speech recognition device.
 - 8
 - 9
 - 10
 - 11
 - 12
 - 13
 - 14
 - 15

ATTORNEY DOCKET NO. 10693RMUS01U (NORT10-00255)
U.S. SERIAL NO. 09/468,138
PATENT

1 2. (Unchanged/Original) An apparatus as defined in claim 1, wherein the given speech
2 element is an element selected from the group consisting of phones, diphones, syllables and words.

1 3. (Unchanged/Original) An apparatus as defined in claim 2, wherein said input signal
2 derived from a spoken utterance is indicative of a speaker specific speech model associated to the
3 at least one speech element.

1 4. (Unchanged/Original) An apparatus as defined in claim 3, wherein said hybrid speech
2 model is weighted toward the speaker specific speech model.

1 5. (Unchanged/Original) An apparatus as defined in claim 4, wherein said hybrid speech
2 model is derived by computing a linear combination of the speech models in said model group.

ATTORNEY DOCKET NO. 10693RMUS01U (NORT10-00255)
U.S. SERIAL NO. 09/468,138
PATENT

1 6. (Unchanged/Original) An apparatus as defined in claim 5, wherein said input is a first
2 input and wherein said input signal is a first input signal, said apparatus further comprising:
3 a) a second input for receiving a second input signal conveying a data element
4 identifying the given speech element;
5 b) a database of model groups comprising a plurality of model groups, each model group
6 being associated to a respective speech element, each model group comprising a set of speech
7 models;
8 said processing unit being further operative for extracting from said database of model groups
9 a certain model group associated to the data element received at said second input identifying the
10 given speech element.

ATTORNEY DOCKET NO. 10693RMUS01U (NORT10-00255)
U.S. SERIAL NO. 09/468,138
PATENT

1 7. (Currently Amended) A method for generating a hybrid speech model associated to a given
2 speech element, said hybrid speech model being suitable for use by a speech recognition device
3 during speech recognition, said method comprising:

4 - receiving an input signal derived from a spoken utterance that contains at least one
5 speech element that potentially matches the given speech element;
6 - providing a model group associated to the given speech element, said model group
7 comprising a plurality of speech models, each speech model of said plurality of
8 speech models being a different representation of the given speech element;
9 - processing the input signal and the model group to generate a hybrid speech model
10 associated to the given speech element, said hybrid speech model being a weighted
11 combination of speech models in said plurality of speech models effected on the basis
12 of the input signal derived from the spoken utterance;
13 - releasing a signal indicative of said hybrid speech model associated to the given
14 speech element in a format suitable for use by a speech recognition device.

ATTORNEY DOCKET No. 10693RMUS01U (NORT10-00255)
U.S. SERIAL No. 09/468,138
PATENT

1 8. (Currently Amended) A computer readable medium comprising a program element suitable
2 for execution by a computing apparatus for generating a hybrid speech model associated to a given
3 speech element, said hybrid speech model being suitable for use by a speech recognition device
4 during speech recognition, said computing apparatus comprising:
5 - a memory unit for storing a model group associated to the given speech element, said
6 model group comprising a plurality of speech models, each speech model of said
7 plurality of speech models being a different representation of the given speech
8 element;
9 - a processor operatively connected to said memory unit, said program element when
10 executing on said processor being operative for implementing:
11 - an input for receiving an input signal derived from a spoken utterance that
12 contains at least one speech element that potentially matches the given speech
13 element;
14 - a processing unit coupled to the input for processing the input signal and the
15 model group to generate a hybrid speech model associated to the given
16 speech element, said hybrid speech model being a weighted combination of
17 speech models in said plurality of speech models effected on the basis of the
18 input signal derived from the spoken utterance;

ATTORNEY DOCKET NO. 10693RMUS01U (NORT10-00255)
U.S. SERIAL NO. 09/468,138
PATENT

19 - an output for releasing a signal indicative of said hybrid speech model
20 associated to the given speech element in a format suitable for use by a
21 speech recognition device.

1 9. (Currently Amended) An apparatus for generating a complex speech model associated to a
2 given speech element, said complex speech model being suitable for use by a speech recognition
3 device during speech recognition, said apparatus comprising:

4 - an input for receiving an input signal derived from a spoken utterance that contains
5 at least one speech element that potentially matches the given speech element;
6 - a model group associated to the given speech element, said model group comprising
7 a plurality of speech models, each speech model of said plurality of speech models
8 being a different representation of the given speech element, said model group
9 comprising two sets of speech models namely a first set having speech models of a
10 first type and a second set having speech models of a second type, each speech model
11 of a first type in said first set being associated to a speech model of the second type
12 in the second set;
13 - a processing unit coupled to the input for:
14 a) processing the input signal and the model group to generate a hybrid speech
15 model associated to the given speech element, said hybrid speech model
16 being a weighted combination of speech models of the first type in said

**ATTORNEY DOCKET No. 10693RMUS01U (NORT10-00255)
U.S. SERIAL NO. 09/468,138
PATENT**

1 10. (Currently Amended) An apparatus as defined in claim 9, wherein any speech model of a
2 second type is indicative of a speech model having a higher complexity than a speech model of a first
3 type to which [it]the respective speech model of a second type is associated.

1 11. (Unchanged/Original) An apparatus as defined in claim 10, wherein the given speech
2 element is indicative of a data element selected from the set consisting of phones, diphones, syllables
3 and words.

ATTORNEY DOCKET NO. 10693RMUS01U (NORT10-00255)
U.S. SERIAL NO. 09/468,138
PATENT

1 12. (Unchanged/Original) An apparatus as defined in claim 11, wherein said input signal
2 derived from a spoken utterance is indicative of a speaker specific speech model associated to the
3 at least one speech element.

1 13. (Unchanged/Original) An apparatus as defined in claim 12, wherein said hybrid
2 speech model is weighted toward the speaker specific speech model.

1 14. (Unchanged/Original) An apparatus as defined in claim 13, wherein said hybrid
2 speech model is derived by computing a linear combination of the speech models of the first type.

1 15. (Unchanged/Original) An apparatus as defined in claim 14, wherein said linear
2 combination is a first linear combination and is characterized by a first set of parameters indicative
3 of weights associated to speech models of the first type, said complex speech model being derived
4 by computing a second linear combination of the speech models of the second type, said second
5 linear combination being characterized by a second set of parameters indicative of weights associated
6 to speech models of the second type.

1 16. (Unchanged/Original) An apparatus as defined in claim 15, wherein said first set of
2 parameters and said second set of parameters are indicative of substantially same weights.

ATTORNEY DOCKET No. 10693RMUS01U (NORT10-00255)
U.S. SERIAL No. 09/468,138
PATENT

1 17. (Unchanged/Original) An apparatus as defined in claim 10, wherein said input is a
2 first input and wherein said input signal is a first input signal, said apparatus further comprising:
3 a) a second input for receiving a second input signal indicative of a data element
4 identifying the given speech element;
5 b) a database of model groups comprising a plurality of model groups, each model
6 group being associated to a respective speech element, each model group comprising
7 two sets of speech models namely a first set having speech models of a first type and
8 a second set having speech models of a second type, each speech model of a first type
9 in said first set being associated to a speech model of the second type in the second
10 set;
11 said processing unit being further operative for extracting from said database of model groups
12 a certain model group associated to the data element received at said second input identifying the
13 given speech element.

ATTORNEY DOCKET NO. 10693RMUS01U (NORT10-00255)
U.S. SERIAL NO. 09/468,138
PATENT

1 18. (Currently Amendment) A computer readable medium comprising:
2 a first data structure for storing a plurality of model groups, each model group being
3 associated to a respective speech element in a phonetic alphabet, each model group comprising a
4 plurality of speech models, each model group being suitable for use by a processing device; and
5 a second data structure for storing a hybrid speech model associated to a given speech
6 element, said hybrid speech model being a weighted combination of speech models of the first type
7 in said plurality of speech models effected on the basis of an input signal derived from a spoken
8 utterance that contains at least one speech element that potentially matches the given speech element.

1 19. (Unchanged/Original) A computer readable medium as defined in claim 18, wherein
2 the given speech element is indicative of a data element selected from the set consisting of phones,
3 diphones, syllables and words.

ATTORNEY DOCKET No. 10693RMUS01U (NORT10-00255)
U.S. SERIAL NO. 09/468,138
PATENT

1 20. (Currently Amended) A computer readable medium as defined in claim 19, wherein each
2 model group comprises two sets of speech models namely a first set having a plurality of speech
3 models of a first type and a second set having a plurality of speech models of a second type, each
4 speech model of a first type in said first set being associated to a speech model of the second type
5 in the second set, each speech model of the second type being indicative of a speech model having
6 a higher complexity [that]than a speech model of the first type to which the speech model of the
7 second type is associated.

**ATTORNEY DOCKET No. 10693RMUS01U (NORT10-00255)
U.S. SERIAL NO. 09/468,138
PATENT**

1 21. (Currently Amended) A speech recognition system comprising:

2 - an input for receiving an input signal indicative of a spoken utterance that is

3 indicative of at least one speech element;

4 - a first processing unit coupled to said input operative for processing the input signal

5 to derive from a speech recognition dictionary at least one speech model associated

6 to a given speech element that constitutes a potential match to the at least one speech

7 element;

8 - a second processing unit coupled to said first processing unit for generating, using

9 a predefined weighting constraint, a modified version of the at least one speech

10 model on the basis of the input signal;

11 - a third processing unit coupled to said second processing unit for processing the input

12 signal on the basis of the modified version of the at least one speech model to

13 generate a recognition result indicative of whether the modified version of the at least

14 one speech model constitutes a match to the input signal;

15 - an output for releasing a signal indicative of the recognition result.

AT

ATTORNEY DOCKET NO. 10693RMUS01U (NORT10-00255)
U.S. SERIAL NO. 09/468,138
PATENT

1 22. (Unchanged/Original) A speech recognition system as defined in claim 21, wherein
2 said first processing unit is operative for generating a speaker specific speech model derived on the
3 basis of the input signal, the speaker specific speech model being indicative of the acoustic
4 characteristics of the least one speech element.

1 23. (Unchanged/Original) A speech recognition system as defined in claim 22, wherein
2 said modified version of the at least one speech model is indicative of a hybrid speech model
3 associated to the given speech element.

ATTORNEY DOCKET NO. 10693RMUS01U (NORT10-00255)
U.S. SERIAL NO. 09/468,138
PATENT

1 24. (Currently Amended) A speech recognition system as defined in claim 23, wherein said
2 second processing unit comprises:

3 - coupling member for allowing data exchange between the first processing unit and
4 the second processing unit, said coupling member being suitable for receiving the
5 speaker specific speech model derived from the input signal;
6 - a model group associated to the given speech element, said model group comprising
7 a plurality of speech models, each speech model of said plurality of speech models
8 being a different representation of the given speech element;
9 - a functional unit coupled to the coupling member for processing the speaker specific
10 speech model and the model group to generate the hybrid speech model associated
11 to the given speech element, said hybrid speech model being a weighted combination
12 of speech models in said plurality of speech models effected on the basis of the
13 speaker specific speech model;
14 - an output coupling member for allowing data exchange between the second
15 processing unit and the third processing unit, said output coupling member being
16 suitable for releasing a signal indicative of the hybrid speech model associated to the
17 given speech element.

AT

**ATTORNEY DOCKET No. 10693RMUS01U (NORT10-00255)
U.S. SERIAL NO. 09/468,138
PATENT**

1 25. (Unchanged/Original) A speech recognition system as defined in claim 24, wherein
2 said hybrid speech model is weighted toward the speaker specific speech model.

1 26. (Unchanged/Original) A speech recognition system as defined in claim 24, wherein
2 said hybrid speech model is derived by computing a linear combination of the speech models in said
3 group of speech models.

1 27. (Unchanged/Original) A speech recognition system as defined in claim 24, wherein

2 said coupling member is a first coupling member, said second processing unit further comprising:

3 a) a second coupling member for allowing data exchange between the first processing

4 unit and the second processing unit, said second coupling member being suitable for

5 receiving a data element identifying the given speech element;

6 b) a database of model groups comprising a plurality of model groups, each model

7 group being associated to a respective speech element, each model group comprising

8 a set of speech models;

9 said functional unit being further operative for extracting from said database of model groups

10 a certain model group associated to the data element received at said second coupling member

11 identifying the given speech element.

ATTORNEY DOCKET NO. 10693RMUS01U (NORT10-00255)
U.S. SERIAL NO. 09/468,138
PATENT

1 28. (Unchanged/Original) A speech recognition system as defined in claim 22, wherein
2 said modified version of the at least one speech model is indicative of a complex speech model
3 associated to the given speech element.

1 29. (Unchanged/Original) A speech recognition system as defined in claim 28, wherein
2 said second processing unit comprises:

- 3 - coupling member for allowing data exchange between the first processing unit and
4 the second processing unit, said coupling member being suitable for receiving the
5 speaker specific speech model derived from the input signal;
- 6 - a model group associated to the given speech element, said model group comprising
7 a plurality of speech models, each speech model of said plurality of speech models
8 being a different representation of the given speech element, said model group
9 comprising two sets of speech models namely a first set having speech models of a
10 first type and a second set having speech models of a second type, each speech model
11 of a first type in said first set being associated to a speech model of the second type
12 in the second set;
- 13 - a functional unit coupled to the coupling member for:
 - 14 a) processing the speaker specific speech model and the model group to
15 generate a hybrid speech model associated to the given speech element, said
16 hybrid speech model being a weighted combination of speech models of the

ATTORNEY DOCKET NO. 10693RMUS01U (NORT10-00255)
U.S. SERIAL NO. 09/468,138
PATENT

17 first type in said plurality of speech models effected on the basis of the
18 speaker specific speech model;
19 b) processing the hybrid speech model to generate a complex speech model
20 associated to the given speech element, said complex speech model being a
21 combination of speech models of the second type in said plurality of speech
22 models;
23 an output coupling member for allowing data exchange between the second
24 processing unit and the third processing unit, said coupling member being suitable
25 for releasing a signal indicative of the complex speech model associated to the given
26 speech element.

1 30. (Currently Amended) A speech recognition system as defined in claim 29, wherein any
2 speech model of the second type is indicative of a speech model having a higher complexity than a
3 speech model of the first type to which [it]the speech model of the second type is associated.

1 31. (Unchanged/Original) A speech recognition system as defined in claim 30, wherein
2 said hybrid speech model is weighted toward the speaker specific speech model.

ATTORNEY DOCKET NO. 10693RMUS01U (NORT10-00255)
U.S. SERIAL NO. 09/468,138
PATENT

1 32. (Unchanged/Original) A speech recognition system as defined in claim 31, wherein
2 said hybrid speech model is derived by computing a linear combination of the speech models of the
3 first type.

1 33. (Unchanged/Original) A speech recognition system as defined in claim 32, wherein
2 said linear combination is a first linear combination and is characterized by a first set of parameters
3 indicative of weights associated to speech models of the first type, said complex speech model being
4 derived by computing a second linear combination of the speech models of the second type, said
5 second linear combination being characterized by a second set of parameters indicative of weights
6 associated to speech models of the second type.

1 34. (Unchanged/Original) A speech recognition system as defined in claim 33, wherein
2 said first set of parameters and said second set of parameters is indicative of substantially the same
3 weights.

ATTORNEY DOCKET No. 10693RMUS01U (NORT10-00255)
U.S. SERIAL NO. 09/468,138
PATENT

1 35. (Currently Amended) An apparatus for generating a hybrid speech model associated to a
2 given speech element, said hybrid speech model being suitable for use by a speech recognition
3 device during speech recognition, said apparatus comprising:
4 - means for receiving an input signal derived from a spoken utterance that contains at
5 least one speech element that potentially matches the given speech element;
6 - a model group associated to the given speech element, said model group comprising
7 a plurality of speech models, each speech model of said plurality of speech models
8 being a different representation of the given speech element;
9 - means for processing the input signal and the model group to generate a hybrid
10 speech model associated to the given speech element, said hybrid speech model being
11 a weighted combination of speech models in said plurality of speech models effected
12 on the basis of the input signal derived from the spoken utterance;
13 - means for releasing a signal indicative of said hybrid speech model associated to the
14 given speech element in a format suitable for use by a speech recognition device.

A/

ATTORNEY DOCKET NO. 10693RMUS01U (NORT10-00255)
U.S. SERIAL NO. 09/468,138
PATENT

1 36. (Currently Amended) A speech recognition system comprising:

2 - means receiving an input signal indicative of a spoken utterance that is indicative of

3 at least one speech element;

4 - means for processing the input signal to derive from a speech recognition dictionary

5 at least one speech model associated to a given speech element that constitutes a

6 potential match to the at least one speech element;

7 - means for generating, using a predefined weighting constraint, a modified version of

8 the at least one speech model on the basis of the input signal;

9 - means for processing the input signal on the basis of the modified version of the at

10 least one speech model to generate a recognition result indicative of whether the

11 modified version of the at least one speech model constitutes a match to the input

12 signal;

13 - means for releasing a signal indicative of the recognition result.

Please add the following new claim(s):

1 37. (Newly Added) An apparatus as defined in claim 15, wherein a relationship between

2 said first set of parameters and said second set of parameters is dependent on a distance between the

3 hybrid model and the input signal.

ATTORNEY DOCKET NO. 10693RMUS01U (NORT10-00255)
U.S. SERIAL NO. 09/468,138
PATENT

1 38. (Newly Added) An apparatus as defined in claim 37, wherein the processing unit
2 further comprises:
3 a fall-back unit conditioning the weighted combination of speech models of the second type
4 by interpolation to a degree based upon a distance between the hybrid model and the input signal.
